



GENERAL NOTES:
1. PIPING CONSTRUCTED TO ASME B31.3 SOUR SERVICE
2. MATERIALS:

WELDED PIPE:
2" & UNDER A-106B, SCH 80
3" TO 10" A-106B, SCH 40
THREADED PIPE:
2" & SMALLER A-106B, SCH 160
FITTINGS:
A-105, 3000# NPT
FLANGES:
A105N, SCH 80, 300#
GASKETS:
SPIRAL WOUND 316 SS GRAPHITE FILLED
TUBING:
3/4" 316SS, .035" WALL
TUBING FITTINGS:

3. PRESSURE TESTED TO 1080 PSIG
4. 100% X-RAY
5. 10% HARDNESS TEST, MAXIMUM VALUE OF 225 BHN

L SKID SIZE" 7'-3"x7'-3"x17'-9" HIGH
COMPLETE SKID AND PIPING IS SAND BLASTED
TO SSPC-6 LEVEL
HIGH TEMP PRIMED AND HIGH TEMP PAINTED SILVER

[illegible]

**STETTLER
OIL & GAS**
PHONE: (403) 742-6686
BOX 652, STETTLER, AB T0C 2L0

AQP-2982	WP-SOG-1
----------	----------

CLIENT	SCIMITAR PRODUCTION EGYPT LTD. PROJECT NUMBER: 109-01-01 ISSARAN PRODUCTION FACILITIES PHASE 2 EXPANSION - SATELLITE: 3000
	3 PHASE SEPARATOR (36" x 120") 4' X 300 ANSI x MAWP 600 PSIG @ -20/500°F, 125 CA PIPING & INSTRUMENTATION DIAGRAM

DATE: 2008-05-05	SETTLER OIL & GAS PROJECT NO. 016296/5	
SCALE: NONE	DRAWING NO. 8-404SS-M-01	REV. 0
DESIGNED BY:		
DRAWN BY: CRJ		
CHECKED BY: JB	SHEET 1 of 5	