

PXT/2

Performance for 95 BHP 3 Stage with 6", 4" 3" Cylinders

Ts = 60 F

Elv 2500 ft

Amb 90 F

IC 120 F

CHP 86 available

Ps	Pd	Flow	BHP	Comments
10	450	0.22	54	
20	450	0.33	70	
30	450	0.44	83	
40	450	0.5	85	
50	450	0.53	85	
60	450	0.57	85	
15	710	0.28	68	
20	710	0.34	77	
25	710	0.4	85	
30	710	0.43	86	
35	710	0.45	86	
40	710	0.46	86	
45	710	0.48	86	
10	900	0.21	60	Td3 323
12	900	0.23	65	Td3 317
14	900	0.25	69	Td3 311
16	900	0.27	73	
22	900	0.34	84	
40	900	0.39	85	
50	1000	0.39	82	
75	1000	0.46	84	
95	1000	0.5	85	
100	1000	0.53	87	over bhp
10	1100	0.2	62	Td3 335
12	1100	0.22	66	Td3 330
14	1100	0.25	70	Td3 325
16	1100	0.27	75	Td3 320
21	1100	0.32	85	
36	1100	0.36	85	
15	1250	0.24	72	Td3 315
20	1250	0.3	82	
40	1250	0.36	85	
45	1250	0.37	85	