



GE Oil & Gas - HSR Compressor Performance Report

Page 1 of 1

Project Name: CES1541
Customer/End-user: Crusader
Packager: Toromont
Site Location: 1-1-1w4

Quote #: n/a
Case #: n/a
Version: 02.02.00
Date: 11/04/2014, 12:29:06 PM

Application Data:	Compressor Frame: DS604	Driver Data:	Site Data:
Est. Flow:: 3.893 MMscfd	Rated Power: 2400.0 HP	Type: Engine	Elevation: 2500.0 ft
Load/Flow: 201.4 HP/MMscfd	Stroke: 6.000 in	Manufacturer: Caterpillar	Atm. Pressure: 13.4110 psiA
Est. Total Load: 784.1 HP (100%)	Rated Speed: 1200	Model: G3512-LE	Ambient Temp: 90.0 deg F
Run Speed: 1200	Rod Diameter: 2.000 in	Rated Power: 810.0 HP	Gas Method: Generic
Auxiliary Load: 25.0 HP(d)	Max Rod Load Comp: 35000 lbf	Rated Speed: 1200	Base Conditions for Flow Rates:
Lubrication: Lubed	Max Rod Load Tens: 35000 lbf	Avail. Power: 785.0 HP	Pressure: 14.6960 psiA
Type: Miscellaneous	Max Rod Load Gas: 42000 lbf	Amb. Derate: Fixed	Temperature: 60.0 deg F
ISSUES: -			
Project Notes: No Gas Analysis Entered,			
Case Notes:			
Order Status:			

Stage/Service Data:	Stage-1	Stage-2	Stage-3
Flow Rate: MMscfd	3.89	3.89	3.89
Load: HP	289.6	262.8	199.7
Specific Gravity: -	0.6500	0.6500	0.6500
K Value (Cp/Cv): -	1.2400	1.2400	1.2400
Zs: -	0.9941	0.9865	0.9635
Zd: -	0.9920	0.9838	0.9604
Suction Press.: psiG	29.00	111.60	328.89
Ps@Flange: psiG	27.73	111.60	328.89
Pd@Flange: psiG	115.35	335.73	810.00
Discharge Press.: psiG	111.60	328.89	800.00
Compress. Ratio: -	3.1300	2.7928	2.4055
Suction Temp.: deg F	60.0	105.0	105.0
Cooler Temp.: deg F	105.0	105.0	n/a

Cylinder Data:	Throw-1	Throw-2	Throw-3	Throw-4	Throw-5	Throw-6
Model: -	95 Series	89 Series	BLANK	95 Series		
Operating Mode: -	D/A Cyl	D/A Cyl	THROW	D/A Cyl		
Head End	Stage	Stg-1	Stg-3	Stg-2		
Bore: in	14.25	5.5	-	9	-	-
MAWP: psiG	800	2200	-	1800	-	-
RDP: psiG	727	2000	-	1636	-	-
Tail Rod Dia: in	0	0	-	0	-	-
Est. Td: deg F	210.6	217.9	-	245.2	-	-
VVCP Open: in : Turns	0.00 : 0	0.00 : 0	-	0.00 : 0	-	-
Base Clr: %	13.43	27.67	-	22.21	-	-
Added Clr: %	0.00	0.00	-	0.00	-	-
Total Clr: %	13.43	27.67	-	22.21	-	-
Vol. Eff. Suct.: %	73.55	66.76	-	66.18	-	-
Vol. Eff. Disch.: %	29.24	32.79	-	28.83	-	-
Flow: MMscfd	1.94	2.09	-	1.97	-	-
Crank End	Stage	Stg-1	Stg-3	Stg-2		
Bore: in	14.25	5.5	-	9	-	-
MAWP: psiG	800	2200	-	1800	-	-
RDP: psiG	727	2000	-	1636	-	-
Est. Td: deg F	210.6	217.9	-	245.2	-	-
Base Clr: %	11.88	28.04	-	20.58	-	-
Added Clr: %	0.00	0.00	-	0.00	-	-
Total Clr: %	11.88	28.04	-	20.58	-	-
Vol. Eff. Suct.: %	75.73	66.40	-	68.15	-	-
Vol. Eff. Disch.: %	30.11	32.61	-	29.69	-	-
Flow: MMscfd	1.96	1.80	-	1.93	-	-
Valve Spacers: HE#/CE#	0 / 0	0 / 0	-	0 / 0	-	-
Rod Loads						
Gas-Compress.: %	43.8	32.7	-	42.1	-	-
Gas-Tension: %	41.2	23.5	-	37.4	-	-
Net-Compress.: %	65.8	64.1	-	44.1	-	-
Net-Tension: %	82.3	83.4	-	46.4	-	-
Pin Reversal: Deg/Mag%	150/80	147/77	-	167/95	-	-
Throw Loading	HP	HP				
	289.6	199.7	-	262.8	-	-

BOLD = Out of Limit FILE: CES1541 th 3 blank.hsr

GE HSR Compressors, its owners, affiliates, authorized distributors or agents assume no liability for any consequences, damages or loss of production as a result of use or misuse of the information or calculations contained in this program.